Data Sheet: EP70 FDA (Vulcanised Jointed rings)

MATERIAL: EPDM 70 SHORE FDA FOR VULCANISED JOINTED RINGS (FDA 21 CFR 177.2600)

Excellent resistance to Oil, Gasoline, Chemicals, Weathering

Low gas permeability. Good water resistance.

COLOUR: BLACK

GENERAL SERVICE TEMPERATURE RANGE: -25°C to +125°C continuous (+150°C peak)

PHYSICAL PROPERTIES	REQUIREMENT	TEST RESULT
SPECIFIC GRAVITY	ASTM D257 TOLERANCE ±0.05	1.28
DUROMETER SHORE A	ISO 7619-1 TOLERANCE ±5°	70
ELONGATION %	DIN 53504 TOLERANCE ±35%	125
TENSILE STRENGTH PSI (MPa)	DIN 53504 TOLERANCE ±25%	14
COMPRESSION SET		
22hrs (a) 120°C %	ISO 815-1 TOLERANCE +25%	20%

MINERAL OIL RESISTANCE NOT RECOMMENDED
ANIMAL OIL RESISTANCE NOT RECOMMENDED
VEGETABLE OIL RESISTANCE NOT RECOMMENDED

WEATHERING RESISTANCE VERY GOOD

The above test results are based on test slabs / buttons. The results from the actual parts may be different.

