## Data Sheet: EP70 (Vulcanised Jointed rings)

## MATERIAL: ETHYLENE PROPYLENE DIENE MONOMER (EPDM) 70 SHORE FOR VULCANISED JOINTED RINGS

Excellent resistance to Oil, Gasoline, Chemicals, Weathering

Low gas permeability. Good water resistance.

**COLOUR: BLACK** 

GENERAL SERVICE TEMPERATURE RANGE: -35°C to +120°C continuous (+160°C peak)

PHYSICAL PROPERTIES	REQUIREMENT	TEST RESULT
SPECIFIC GRAVITY	ASTM D257 TOLERANCE ±0.05	1.28
DUROMETER SHORE A	ISO 7619-1 TOLERANCE ±5°	70
ELONGATION %	DIN 53504 TOLERANCE ±35%	500
TENSILE STRENGTH PSI (MPa)	DIN 53504 TOLERANCE ±25%	14
COMPRESSION SET		
22 hrs @ 70°C, %	ISO 815-1 TOLERANCE ±25%	21%
MINERAL OIL RESISTANCE	NOT RECOMMENDED	
12 12 0.2.1.20.0 102		
ANIMAL OIL RESISTANCE	NOT RECOMMENDED	
VEGETABLE OIL RESISTANCE	NOT RECOMMENDED	
WEATHERING RESISTANCE	VERY GOOD	

The above test results are based on test slabs / buttons. The results from the actual parts may be different.

