

O-ring Cord

O-Ring Cord is supplied as a continuous extruded cord and can be used to make custom sized O-Rings when standard sizes are not suitable.

O-Ring Cord, or extruded cord is one of our major stock lines. We hold large stocks of Nitrile, FKM and Silicone Cords from 1.00 mm - 25.00 mm in standard shore hardness's with larger diameters available on request. Additional materials including DuPont Viton® Cord are also available on request.

We also have an expanding stock range of both Silicone and EPDM cords. Our vast availability of cord stocks ensures we can provide same day despatch and next day delivery at competitive prices.

Square Section and 4 Lobed Profile (Quad-ring®) Cord is also available in sizes up to 25 mm and various shore hardness's.

Additional materials can be supplied on short lead times upon request:

- Aflas® (in both 75 and 90 Shore)
- Fluorosilicone
- Polyurethane
- HNBR 70

All our cord can be supplied in bulk on spools or cut to length as required; the spool lengths vary by size, so ask when ordering.

Butt joined rings are available upon request and can be turned round within 24 hours or less.

We can also supply standard spicing kits in Viton® and Nitrile, however, other materials can be provided.



Figure 1.1 Splicing Kits available

“ We hold **large stocks of Nitrile and Viton® O-ring Cord**, as well as other materials including **Silicone and EPDM**. We also supply **Vulcanised O-rings**. ”